



## APPLICATION

The twin paddles on the drum agitator fold back to fit through the bung on standard containers. TMI recommends this type of appliance for small volumes and simple mixing applications. The type of agitator is determined by the required application. We supply with three-phase 50 Hertz tropicalized motors as standard. The standard impeller shaft is made from 316L stainless steel. The agitator can be inserted through a 60 mm or wider bung opening for greater versatility if required.

A polypropylene or PVC clamp is included for attaching the motor unit to the drum.

## OPTIONS

- Other voltages
  - 60 Hz
  - Atex motor
  - Compressed air motor
  - Single-phase motor
  - Power cord and plug
  - High-specification materials (Uranus 52N, Uranus B6, etc)
  - Other options are available according to requirements.
- Contact us for information.

## SUMMARY

- Agitateur pour fût avec pâles rétractables
  - Diamètre minimum de passage 60 millimètres
  - Traitement en bâchée 1 heure par jour
  - Volume max 200 Litres
- Standard 230/400 V • Triphasé 50 Hz Tropicalisé

# TECHNICAL DATA

Type	Ø Impeller	P (kw)	N (tr/min)	Q (m3/h)	Weight (kg)
AFS 12 285T	12C	0,12	285	14	8
AFS 12 285M	12C	0,12	299	15	9

> Drawing for illustration purposes

